

**SAFETY DATA SHEET**  
WhisperTrack<sup>®</sup>

**SECTION 1 - PRODUCT AND COMPANY IDENTIFICATION**

|                                                |                                                                                                         |
|------------------------------------------------|---------------------------------------------------------------------------------------------------------|
| <b>PRODUCT NAME:</b> WhisperTrack <sup>®</sup> | <b>PVC Compounds</b><br><b>3000 thru 9499 and 85813</b><br><b>Pellet and Powder, all colours</b>        |
| <b>SYNONYMS:</b>                               | Polyvinyl chloride compound, chloroethylene homopolymer compound                                        |
| <b>CHEMICAL FORMULA:</b>                       | (C <sub>2</sub> H <sub>3</sub> Cl), plus functional derivatives                                         |
| <b>MANUFACTURER / SUPPLIER:</b>                | Whisper Walls<br>10957 East Bethany Drive<br>Aurora, CO USA 80014<br>Phone Number: (303) 671-6696       |
| <b>EMERGENCY PHONE NUMBER:</b>                 | For transportation emergencies:<br>CHEMTREC (800) 424-9300<br>For all other emergencies: (905) 761-8529 |
| <b>PREPARED BY:</b>                            | NAPC in conjunction with a third party consultant                                                       |
| <b>PRODUCT USE:</b>                            | Feedstock for PVC processing                                                                            |
| <b>DATE OF PREPARATION:</b>                    | November 29, 2022                                                                                       |

**SECTION 2 – HAZARDS IDENTIFICATION**

|                        |                                                                                                                                                                                                  |
|------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>CLASSIFICATION:</b> | Combustible Dusts – Category 1<br>Germ Cell Mutagen – Category 2<br>Carcinogenicity – Category 2<br>Reproductive Toxicity – Category 2<br>Target Organ Toxicant – Repeated Exposure – Category 2 |
|------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|

**GHS LABEL SYMBOL:**



|                           |                                                                                                             |
|---------------------------|-------------------------------------------------------------------------------------------------------------|
| <b>HAZARD STATEMENTS:</b> | Warning – May form combustible dust concentrations in air<br>Warning – Suspected of causing genetic defects |
|---------------------------|-------------------------------------------------------------------------------------------------------------|

Warning – Suspected of causing cancer by inhalation  
 Warning – Suspected of damaging fertility or the unborn child  
 Warning – May cause damage to organs through prolonged or repeated exposure by inhalation

**PRECAUTIONARY STATEMENTS:**
**Prevention**

P201 – Obtain special instructions before use  
 P202 – Do not handle until all safety precautions have been read and understood  
 P260 – Do not breathe dust/vapours  
 P270 – Do not eat, drink or smoke when using this product  
 P280 – Wear respiratory protection

**Response**

P308+P313 If exposed or concerned, get medical attention  
 P314 – Get medical advice/attention if you feel unwell

**Disposal**

P501 – Dispose of contents/container in accordance with local/provincial/federal regulations

Rigid PVC Compound, in the form of a powder, may present a limited risk of dust explosion when mixed with air, but only under particular conditions. A strong energy source is necessary for ignition. Avoid dispersing the dust into clouds when extinguishing a fire. If proper procedures for processing PVC compounds are not followed, processing fumes and vapors can be liberated at elevated temperatures. The presence of these fumes or vapors may result in worker exposure. Additionally, the composition of these fumes or vapors may vary widely according to the individual processing procedures and materials used. Processors must determine for themselves the appropriate equipment and procedures for their use.

### SECTION 3 – COMPOSITION/INFORMATION ON INGREDIENTS

| CHEMICAL IDENTITY         | CONCENTRATION<br>(PERCENT WEIGHT/WEIGHT) | CAS NUMBER |
|---------------------------|------------------------------------------|------------|
| Polyvinyl chloride resin  | >65                                      | 9002-86-2  |
| Organotin or Calcium-zinc | <5                                       | Mixture    |
| Proprietary additives     | <30                                      | Mixture    |

### SECTION 4 - FIRST AID MEASURES

**INHALATION:** No adverse effects anticipated under normal conditions if adequately ventilated. However, if exposure occurs, remove victim to fresh air. Obtain medical attention if irritation persists.

**SKIN CONTACT:** No adverse effects anticipated under normal conditions. However, if vapor or fume exposure occurs, wash skin thoroughly with soap and water. Obtain medical attention if irritation persists.

**EYE CONTACT:** In the event of eye irritation, flush eyes with water for at least 15 minutes. Do not rub the eyes. Obtain medical attention if irritation persists.

**INGESTION:** If ingestion occurs, vomiting can be induced after diluting gastric

**PERSONAL PROTECTIVE EQUIPMENT FOR FIRST AID RESPONDERS:**

fluids with water or milk. Call a physician for additional medical advice.

In case of significant contamination of victim, wear respiratory protection (minimum of half-facepiece respirator equipped with P100 cartridges) and avoid inhaling product.

## SECTION 5 – FIRE FIGHTING MEASURES

**SUITABLE EXTINGUISHING MEDIA:**

Carbon dioxide or water. Use extinguishing measures that are appropriate to the local circumstances and the surrounding environment.


**SPECIFIC HAZARDS:**

Dense smoke may be emitted when burned. Rigid PVC Compounds will not normally continue to burn after ignition without an external fire source. Rigid PVC Compound, in the form of a powder, may present a limited risk of dust explosion when mixed with air, but only under particular conditions. A strong energy source is necessary for ignition. Avoid dispersing the dust into clouds when extinguishing a fire. Do not allow firefighting runoff water to enter streams, rivers or lakes. The water may collect hydrogen chloride (HCl) and other combustion products. **See Section 10 for additional information.**

Not applicable

**SPECIAL PROTECTIVE ACTIONS FOR FIREFIGHTERS:**

Wear full bunker gear including a positive pressure self-contained breathing apparatus in any closed space.



Flammability Code 1: Must be pre-heated before ignition can occur. Flash point over 93°C (200°F)

Health Code 2: Exposure could cause temporary incapacitation of possible residual injury

Reactivity Code 0: Normally stable, even under fire exposure conditions, and is not reactive with water.

Special Hazards: None

## SECTION 6 – ACCIDENTAL RELEASE MEASURES

**PERSONAL PRECAUTIONS:**

Remove unnecessary personnel from the release area. Wear appropriate personal protective equipment. Refer to Section 8 for details.

**ENVIRONMENTAL PRECAUTIONS:**

Contain material to prevent contamination of the soil, surface water or ground water.

**METHODS AND MATERIALS FOR CONTAINMENT AND CLEANING UP:**

Cleanup uncontaminated material and recycle into process. Clean spills in a manner that does not disperse dust into the air. Spill area can be washed with water. Place unusable material into a closed, properly labeled container compatible with the product. See MSDS Section 15 for Regulatory Information. Minimize dust generation.

## SECTION 7 – HANDLING AND STORAGE

**HANDLING PROCEDURES AND EQUIPMENT:**

Avoid contact with eyes. Avoid breathing dust. Minimize dust generation and accumulation. Employees working with dried polymer should wear respiratory protective equipment.

Wash thoroughly after handling. PVC resin processing may result in the release of low levels of vinyl chloride. Use only in well-ventilated areas.

**STORAGE REQUIREMENTS:**

Store in a dry place away from direct sunlight, heat, and incompatible materials. Store away from food and beverages. Reseal containers immediately after use. Store in a well-ventilated, cool area equipped with high volume sprinkler heads.

PVC dust is capable of propagating a secondary dust explosion. This potential can be reduced by good housekeeping, prevention of dust from process equipment, preventing accumulation of dust on overhead horizontal surfaces and eliminating potential ignition sources.

Avoid heat, flames, sparks, and other sources of ignition. Use properly grounded electrically conductive materials for piping circuits and equipment.

**PACKAGING:**

Not applicable

**SENSITIVITY TO MECHANICAL IMPACT:**

No

Local and state/provincial regulations regarding the handling and storage of chemicals may vary widely. The user should acquire knowledge of these and other appropriate federal and state/provincial laws and regulations as well as consult with the proper authority for guidance in developing adequate handling procedures and constructing appropriate storage facilities.

## SECTION 8 – EXPOSURE CONTROLS/PERSONAL PROTECTION

**EXPOSURE LIMITS:**
**Occupational Exposure Limits (OEL)**

|                                                                 | <i>ACGIH<sup>a</sup></i><br><i>TLV-TWA<sup>b</sup></i>                                         | <i>Ontario</i><br><i>TWA<sup>c</sup></i>                             |
|-----------------------------------------------------------------|------------------------------------------------------------------------------------------------|----------------------------------------------------------------------|
| Polyvinyl Chloride                                              | 1 mg/m <sup>3</sup> , Respirable                                                               | 1 mg/m <sup>3</sup> , Respirable                                     |
| Particles Not Otherwise Specified (insoluble or poorly soluble) | 3 mg/m <sup>3</sup> , Respirable <sup>d</sup><br>10 mg/m <sup>3</sup> , Inhalable <sup>d</sup> | 3 mg/m <sup>3</sup> , Respirable<br>10 mg/m <sup>3</sup> , Inhalable |

The following materials may be present in this product, but are not anticipated to exceed exposure limits under normal conditions:

|                                      |                                 |                                 |
|--------------------------------------|---------------------------------|---------------------------------|
| Carbon Black                         | 3 mg/m <sup>3</sup> , Inhalable | 3 mg/m <sup>3</sup> , Inhalable |
| Titanium Dioxide                     | 10 mg/m <sup>3</sup>            | 10 mg/m <sup>3</sup>            |
| Antimony compounds                   | 0.5 mg/m <sup>3</sup>           | 0.5 mg/m <sup>3</sup>           |
| Barium compounds                     | 0.5 mg/m <sup>3</sup>           | 0.5 mg/m <sup>3</sup>           |
| Arsenic compounds                    | 0.01 mg/m <sup>3</sup>          | 0.01 mg/m <sup>3</sup>          |
| Chromium, metal and Cr III compounds | 0.5 mg/m <sup>3</sup>           | 0.5 mg/m <sup>3</sup>           |
| Tin, organic compounds               | 0.1 mg/m <sup>3</sup>           | 0.1 mg/m <sup>3</sup>           |

|                        |                      |                      |
|------------------------|----------------------|----------------------|
| Hydrogen Chloride      | 2 ppm C <sup>e</sup> | 2 ppm C <sup>e</sup> |
| Vinyl Chloride monomer | 1 ppm                | 1 ppm                |

- a – American Conference of Governmental Industrial Hygienists
- b – Threshold Limit Value - Time Weighted Average (i.e. 8 hours)
- c – Time Weighted Average (i.e. 8 hours) Limit
- d – As a guideline only (i.e. TLV has been withdrawn)
- e – Ceiling limit

**PERSONAL PROTECTIVE EQUIPMENT (PPE):**
**GLOVES (SPECIFY):**

If prolonged skin contact is possible, wear gloves. Wash hands following contact with this product.

**RESPIRATOR (SPECIFY):**

For most conditions, no respiratory protection should be needed. However, in cases of dust formation, NIOSH-approved respiratory protection meeting the requirements of your jurisdiction may be needed. If the material is overheated and starts smoldering, wear a positive pressure self-contained breathing apparatus for respiratory protection.

See CSA Standard Z94.4-11 "*Selection Care and Use of Respirators*" or the "*NIOSH Guide to the Selection and Use of Particulate Respirators (1996)*" for additional information.

**EYE (SPECIFY):**

Wear safety glasses with side shields or goggles. Under high dust conditions, wear monoframe goggles for dust and splash protection or a full-facepiece respirator. See CSA Standard Z94.3-07 (R2012) "*Eye and Face Protectors*" or ANSI/ISEA Z87.1-2010 "*American National Standard for Occupational and Educational Personal Eye and Face Protection Devices*" for additional information.

**FOOTWEAR (SPECIFY):**

As required

**OTHER EQUIPMENT (SPECIFY):**

Wash contaminated clothing before reusing.

**ENGINEERING CONTROLS (E.G. VENTILATION, ENCLOSED PROCESS, SPECIFY):**

Provide general and/or local exhaust ventilation to control airborne levels below the exposure guidelines. Adequate ventilation should be provided as conditions warrant. Local exhaust ventilation should comply with jurisdictional regulations and the American Conference of Governmental Industrial Hygienists, Industrial Ventilation - A Manual of Recommended Practice.

## SECTION 9 - PHYSICAL AND CHEMICAL PROPERTIES

|                                                |                    |
|------------------------------------------------|--------------------|
| <b>PHYSICAL STATE:</b>                         | Pellets or powder  |
| <b>ODOUR AND APPEARANCE:</b>                   | Odourless to mild. |
| <b>ODOUR THRESHOLD:</b>                        | Not available      |
| <b>SPECIFIC GRAVITY (WATER=1):</b>             | 1.25 to 1.55       |
| <b>SOLUBILITY IN WATER</b>                     | Not water soluble  |
| <b>CO-EFFICIENT OF WATER/OIL DISTRIBUTION:</b> | Not available      |
| <b>VAPOUR PRESSURE:</b>                        | <0.1               |
| <b>BOILING POINT (°C):</b>                     | Not applicable     |
| <b>MELTING/FREEZING POINT (°C):</b>            | Not available      |

|                                     |                            |
|-------------------------------------|----------------------------|
| PH:                                 | Not applicable             |
| VAPOUR DENSITY (AIR=1):             | Not applicable             |
| EVAPORATION RATE (BUTYL ACETATE=1): | Not applicable             |
| FLASHPOINT (°C) AND METHOD:         | Not applicable             |
| UPPER FLAMMABLE LIMIT (%):          | Not available              |
| LOWER FLAMMABLE LIMIT (%):          | Not available              |
| AUTO-IGNITION TEMPERATURE (°C):     | Greater than 315°C (600°F) |

## SECTION 10 – STABILITY AND REACTIVITY

|                                   |                                                                                                                                                                                                                                                                                                        |
|-----------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| REACTIVITY:                       | Stable under normal conditions                                                                                                                                                                                                                                                                         |
| CHEMICAL STABILITY:               | Normally stable. Hazardous polymerization will not occur.                                                                                                                                                                                                                                              |
| CONDITIONS TO AVOID:              | Instantaneous temperatures above 215°C (420°F), prolonged heating at processing temperatures, or excessive shear/heat combinations during processing can generate hazardous decomposition products.                                                                                                    |
| INCOMPATIBLE MATERIALS:           | Polyvinyl chloride compounds should not come into contact with acetal or acetal copolymers in elevated temperature processing equipment. The two materials are not compatible and <b>will react in a violent decomposition</b> when mixed under conditions of heat and pressure.                       |
| HAZARDOUS DECOMPOSITION PRODUCTS: | Overheating may cause thermal degradation of PVC compound. Fumes and vapors (including CO, CO <sub>2</sub> , and HCl) may be generated during this thermal degradation. Emissions are also possible during normal operating conditions, and may accumulate within an inadequately ventilated facility. |

## SECTION 11 – TOXICOLOGICAL INFORMATION

|                                    |                                                                                                                                                                                                                                                                                                                                                                                                                                  |
|------------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| ROUTE OF ENTRY:                    | <input checked="" type="checkbox"/> Skin Contact <input type="checkbox"/> Skin Absorption <input checked="" type="checkbox"/> Eye Contact <input checked="" type="checkbox"/> Inhalation<br><input type="checkbox"/> Ingestion                                                                                                                                                                                                   |
| ACUTE TOXICITY:                    | Dust associated with the handling of PVC powder as well as fumes or vapors liberated from both PVC powder and pellets at high temperatures may be irritating to the eyes, skin and respiratory tract if not adequately ventilated.<br><br>Measures of acute toxicity are as follows:<br>Lowest Toxic Dose, Oral (TD <sub>LO</sub> ) 210 g/kg, rat<br>50% Lethality, Inhalation (LC <sub>50</sub> ) 140 mg/m <sup>3</sup> , mouse |
| SKIN CORROSION/IRRITATION:         | Vapors or fumes emitted during processes involving elevated temperatures may cause skin irritation. Dust resulting from the handling of powder may be irritating to the skin.                                                                                                                                                                                                                                                    |
| SERIOUS EYE DAMAGE/IRRITATION:     | Vapors or fumes emitted, due to other than normal processing conditions, may cause eye irritation. Dust resulting from the handling of powder may be irritating to the eyes.                                                                                                                                                                                                                                                     |
| RESPIRATORY OR SKIN SENSITIZATION: | Not available                                                                                                                                                                                                                                                                                                                                                                                                                    |
| INTERACTIVE EFFECTS:               | Not available                                                                                                                                                                                                                                                                                                                                                                                                                    |
| MUTAGENICITY:                      | Organotin compounds have been identified as germ cell mutagens.                                                                                                                                                                                                                                                                                                                                                                  |

**CARCINOGENICITY:**

IARC has determined that there is inadequate evidence of carcinogenicity of a polyvinyl chloride resin in both animals and humans. The overall evaluation of polyvinyl chloride is Group 3, meaning that it is not classifiable as a carcinogen (IARC Vol. 19, 1987). Polyvinyl chloride is not listed as a carcinogen by OSHA, NIOSH, NTP, IARC or EPA.

Titanium dioxide is listed as a Group 2B carcinogen – possibly carcinogenic to humans.

**REPRODUCTIVE TOXICITY:**

Organotin compounds have been identified as reproductive toxicants in animal testing. Increases in fetal loss and birth defects were observed..

**SPECIFIC TARGET ORGAN TOXICITY – SINGLE EXPOSURE:**

Not available

**SPECIFIC TARGET ORGAN TOXICITY – REPEATED EXPOSURE:**

Chronic exposure to fumes and vapors from heated or thermally decomposed plastics may cause an asthma-like syndrome due to the inhalation of process vapors or fumes. The onset of irritation maybe delayed for several hours. Fumes or vapors may accumulate within the facility during normal operating procedures that involve elevated temperatures. Exposure to these elevated concentrations, if not adequately ventilated, may have significant health effects.

**ASPIRATION HAZARD:**

Not available. Not expected to be of concern.

## SECTION 12 – ECOLOGICAL INFORMATION

**ECOTOXICITY:**

Based on the high molecular weight of this polymeric material, transport of this compound across biological membranes is unlikely. Accordingly, the probability of environmental toxicity or bioaccumulation in organisms is remote. Due caution should be exercised to prevent the accidental release of this material to the environment.

**PERSISTENCE / DEGRADABILITY:**

Not subject to biodegradation

**BIOACCUMULATION / ACCUMULATION:**

Not available

**MOBILITY IN ENVIRONMENTAL MEDIA:**

Not available

**OTHER ADVERSE EFFECTS:**

Not available

## SECTION 13 – DISPOSAL CONSIDERATIONS

**DISPOSAL:**

Do not dump into any sewers, on the ground, or into any body of water. Waste should be disposed of in accordance with local environmental regulations. Waste characterization and compliance with applicable laws are the responsibility of the waste generator.

## SECTION 14 – TRANSPORTATION INFORMATION

**UN NUMBER:**

Not available

**UN PROPER SHIPPING NAME:**

Polyvinyl Chloride

**TRANSPORT HAZARD CLASSES:**

Not available

**PACKING GROUP:**

Not available

**ENVIRONMENTAL HAZARDS:**

Not available

**SPECIAL PRECAUTIONS FOR USER:**

Not available

## SECTION 15 – REGULATORY INFORMATION

Regulatory information is not meant to be all-inclusive. It is the user's responsibility to ensure compliance with federal, state or provincial and local laws

**SARA TITLE III:**
**Section 302 and 304 of the Act; Extremely Hazardous Substances (40 CFR 355)**

| <u>Component</u> | <u>CAS No.</u> | <u>TPQ<sup>a</sup> (lbs)</u> | <u>RQ<sup>b</sup> (lbs)</u> |
|------------------|----------------|------------------------------|-----------------------------|
| None             | N/A            | N/A                          | N/A                         |

a – Threshold Planning Quantity

b – Reportable Quantity

Specific state and local requirements regarding reportable quantities should be reviewed prior to chemical use, as they may differ from the federal reportable quantity requirement as stated above.

**Section 311 Hazard Categorization (40 CFR 370):**

| <u>Acute</u> | <u>Chronic</u> | <u>Fire</u> | <u>Pressure</u> | <u>Reactive</u> |
|--------------|----------------|-------------|-----------------|-----------------|
| Not Listed   | N/A            | N/A         | N/A             | N/A             |

**SECTION 313 TOXIC CHEMICALS (40 CFR 372.65):**

This product contains the following EPCRA Section 313 chemicals subject to the reporting requirements of Section 313 of the Emergency Planning and Community Right-to-Know Act of 1986.

| <b>COMPONENT</b>   | <b>CAS No.</b> | <b>Weight (percent)</b> |
|--------------------|----------------|-------------------------|
| Antimony Compounds | N010           | 0-20                    |
| Barium Compounds   | N040           | 0-10                    |
| Zinc Compounds     | N982           | 0-10                    |

**CERCLA:**
**Section 102(a) Hazardous Substances (40 CFR 302.4)**

| <u>Component</u> | <u>CAS No.</u> | <u>Weight (lbs)</u> | <u>RQ (lbs)</u> |
|------------------|----------------|---------------------|-----------------|
| None             | N/A            | N/A                 | N/A             |

**RCRA:**

This product, as supplied, is not a hazardous waste according to the USEPA's Toxicity Characteristic Leaching Procedure. Any physical or chemical modification of this product may change the TCLP test results.

**PROPOSITION 65:**

This product contains substances known to the State of California to cause cancer and/or reproductive toxicity.

**CANADIAN REGULATIONS:**

This product has been classified in accordance with the hazard criteria of the *Hazardous Products Regulations* and the SDS contains all the information required by the *Hazardous Products Regulations*.

**CANADIAN ENVIRONMENTAL PROTECTION ACT (CEPA):**

All substances in this product are listed on the Canadian Domestic Substances (DSL) list or are not required to be listed.

**OSHA 29 CFR 1910.1017:**

This compound may contain trace levels (<0.001%) of vinyl chloride monomer (VCM). Under normal working conditions with adequate ventilation, neither the OSHA-PEL of 1 ppm (8-hr TWA), nor the OSHA-STEL (5.0 ppm) should be exceeded. The workplace should be monitored and if the level exceeds any of the PELs or action levels, refer to 29 CFR 1910.1017.



**SECTION 16 – OTHER INFORMATION****SDS VERSION#:**

November 17, 2022 (Version #2)

**IMPORTANT:** The information and data herein are believed to be accurate and have been compiled from sources believed to be reliable. It is offered for your consideration, investigation and verification. Buyer assumes all risk of use, storage, handling and disposal of the product in compliance with applicable federal, state, and local laws and regulations. **Whisper Walls MAKES NO WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, CONCERNING THE ACCURACY OR COMPLETENESS OF THE INFORMATION AND DATA HEREIN.** Energi Fenestration Solutions will not be liable for claims relating to any party's use of or reliance on information and data contained herein regardless of whether it is claimed that the information and data are inaccurate, incomplete or otherwise misleading. This information relates to the material designated and may not be valid for such material used in combination with any other materials nor in any process