

Description

The Whisper Walls WhisperTrack® polymer track, or "stretching system", is a key component to Whisper Walls site-fabricated panels. The WhisperTrack® creates a cavity for core material to be installed that can absorb, reflect, diffuse or be a tackable surface as required. The track is cut in-the-field according to the site conditions and the panel layouts specified. The track securely grips the chosen fabric allowing it to be stretched over the core material creating the tailored appearance and performance that are hallmarks of a Whisper Walls installation.

The WhisperTrack[®] system consists of more than 70 unique track profiles making it the largest and most diverse system available. The individual track components are engineered to work together as a cohesive system that will conform to unique project conditions including angles, curves, penetrations and performance requirements.



Properties

Available in 1/2", 9/16", 3/4", 1", 1 1/8", 1 1/4", 1 1/2" and 2" track heights with other heights achievable by furring up of standard profiles.

Edge conditions: Bevel, radius, square, reveal and welted

See the Whisper Walls website – Details & Specs – Detail Drawings drop down menu for system design details.

Specialty track profiles for the construction of baffles, clouds, art panels and removable tack panels are available.

Class A fire rated - Tested as a stretched fabric panel assembly according to ASTM-E84 and ASTM-E2573 fire test standards.

PVC Free available in select tracks.

Recycled Content

100% Post-Industrial recycled content in most track profiles.

100% Recyclable

VOC

Low VOC rated in 1" system.