

COMPLIANCE TESTED by berkeley analytical

VOC Emission Test Certificate

Product Name: Whisper Walls WhisperTrack PVC Free Stretching System - PVC Free Square Edge System

Product Sample Information		Certificate Information		
Company:	Whisper Walls	Certificate No:	231222-10	
Company Website:	www.whisperwalls.com	Certified By:	far: F	
Product Type:	Stretched-Fabric Wall & Ceiling System		Raja S. Tannous, Laboratory Director	
Date Produced:	11/29/2023	Date:	December 22, 2023	

Reference Standard & Modeling Scenario: California Department of Public Health CDPH/EHLB/Standard Method Version 1.2, 2017 (Emission testing method for CA Specification 01350); Section 4.3.6, Company defined application, see attached Company statement

Acceptance Criteria and Results Demonstrating Compliance of Product Sample to Referenced Standard:

Exposure Scenario ¹	Individual VOCs of Concern ²		Formaldehyde ³		TVOC ⁴
	Criterion	Compliant?	Criterion	Compliant?	Range
School Classroom	≤½ Chronic REL	YES	≤9.0 µg/m³	YES	≤ 0.5 mg/m ³
Private Office	≤½ Chronic REL	YES	≤9.0 µg/m³	YES	≤ 0.5 mg/m ³

Sample Coverage⁵: Not applicable

1. Exposure scenarios & product quantities for classroom & office are defined in Tables 4-2 – 4-5 (CDPH Std. Mtd. V1.2-2017)

2. Maximum allowable concentrations of individual target VOCs are specified in Table 4-1 (*ibid*.)

3. Maximum allowable formaldehyde concentration is ≤9 µg/m³, effective Jan 1, 2012; previous limit was ≤16.5 µg/m³ (ibid.)

4. Informative only; predicted TVOC Range in three categories, i.e., ≤0.5 mg/m³, >0.5 – 4.9 mg/m³, and ≥5.0 mg/m³

5. Informative and applicable only to tests of wet-applied products; grams of sample applied per square meter of substrate

Standards & Codes Recognizing CDPH Standard Method V1.2 (partial list)

- IISGRC I FFD Version 4/4.1 RD&C ID&C Residential RD&C Multifamily
- The WFIT Building Standard, WFIT v2. Feature X06
- ANSI/GRI 01-2019 Green Globes Assessment Protocol

Narrative: Whisper Walls selected a sample representative of its Whisper Walls 1" WhisperTrack PVC Free Stretching System - PVC Free Square Edge System product and submitted it on 11/30/2023 for testing. Berkeley Analytical measured and evaluated the emissions of VOCs from this sample following CDPH/EHLB/Standard Method V1.2-2017. The results of the test are presented in Berkeley Analytical report, 137-004-01A-Dec2223.

Berkeley Analytical is an independent, third-party laboratory specializing in the analysis of organic chemicals emitted by and contained in building products, finishes, furniture, and consumer products. We are an ISO/IEC 17025 accredited laboratory (IAS, <u>TL-383</u>); all standards used in performing this test are in Berkeley Analytical's scope of accreditation.

DISCLAIMER: THIS CERTIFICATE OF COMPLIANCE AFFIRMS THAT: 1) A SAMPLE OF THE LISTED PRODUCT WAS TESTED ACCORDING TO THE REFERENCED STANDARD; 2) THE MEASURED VOC EMISSIONS FROM THE SAMPLE WERE EVALUATED FOR THE DEFINED EXPOSURE SCENARIO(S); AND 3) THE RESULTS MEET THE ACCEPTANCE CRITERIA OF THE REFERENCED STANDARD(S). BERKELEY ANALYTICAL IS NOT RESPONSIBLE FOR ANY CLAIMS REGARDING A PRODUCT OR PRODUCTS ENTERED INTO COMMERCE THAT MAY BE BASED ON THIS TEST. BERKELEY ANALYTICAL PROVIDES THIS CERTIFICATE OF COMPLIANCE "AS IS" WITHOUT WARRANTY OF ANY KIND, EITHER EXPRESSED OR IMPLIED, INCLUDING BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY OR FITNESS FOR ANY PURPOSE.

©2019 Berkeley Analytical, 815 Harbour Way South, Suite 6, Richmond, CA 94804 / 510-236-2325 / www.berkeleyanalytical.com



10957 East Bethany Drive, Aurora, Colorado 80014 303-671-6696

December 4, 2023

Berkeley Analytical 815 Harbour Way South, Unit 6 Richmond, CA 94804-3614

RE: Statement of product quantities to be used to model and determine compliance of test results with VOC emission guidelines in CDPH Standard Method V1.2

Below are the rational and the calculations for quantity of the Whisper Walls 1" WhisperTrack PVC Free Square Edge Stretching System components used in Whisper Walls Stretched-Fabric Wall System, which would be used in the standard school classroom and the standard private office defined in CDPH Standard Method V1.2.

CLASSROOM

While it is typical that only one or two walls may be covered in the Whisper Walls Stretched-Fabric Wall System, the worst case in a Classroom of 40' x 24' x 8.5' would be that all four walls would be covered. If four walls had Whisper Walls on the 1088 SF of wall surface, there would be approximately 631 lineal feet of the Whisper Walls 1" Square Edge Stretching System installed.

PRIVATE OFFICE

While it is typical that only one or two walls may be covered in the Whisper Walls Stretched-Fabric Wall System, the worst case in an Office of 12' x 10' x 9' would be that all four walls would be covered. If four walls had Whisper Walls on the 414 SF of wall surface, there would be approximately 240 lineal feet of the Whisper Walls 1" Square Edge Stretching System installed.

Please feel free to contact me if you have any questions regarding this information.

Sincerely,

Buld. St

Brad Enter President